


3348 Route 208, Campbell Hall, NY 10916 Phone: 845-496-1600 Fax: 845-496-1398

12960 Commerce Lake Drive, A14, Fort Myers, FL 33 42 Day Farm Road, West Stockbridge, MA 01266 1813 State Route 7, Harpursville, NY 13787

			1010 50000 110000 1,1	2002 p 0025 (1212	0,
CLIENT:	Aden Aggregates			PROJECT NO.:	240511
PROJECT:	2024 Quality Control		LAB NUMBER:	24-0660B-1	
TEST METHOD:	ASTM D 1557 'M	Iodifi	ed Proctor'	Method: C	
Manual or Automatic Method	Automatic Metho	d	Type of Hammer Face	Sector Face	
SOIL ID NUMBER:	2				
ITEM:	Screened Fill				
SOURCE:	Grasso Quarry				
SOIL DESCRIPTION:	Brown Silty Sand & Gravel: 44% Gravel; 31% Sand; 25% Silt				
DATE SAMPLED:	6/20/2024		SAMPLED BY:	Client	•
DATE TESTED:	6/24/2024		TESTED BY:	Mike Thomas / Mara	M

REPORT OF MOISTURE DENSITY RELATIONSHIP



Moisture	Content,	70	IJУ	Dry	wiass

Individual Test Points		
Percent	Dry	
Moisture	Density	
5.5	124.5	
7.8	129.5	
9.4	132.6	
11.3	127.5	

Uncorrected Maximum Dry Density:	132.6	lb/cu. ft.
Uncorrected Optimum Moisture Content:	9.6	%
Specific Gravity of Soils *:	2.75	
Percent Oversize Particles:	14.2	%
Est. Specific Gravity of Oversize*:	2.67	

Corrected* Maximum Dry Density:	136.6	lb/cu. ft.
Corrected* Opt. Moisture Content:	8.4	%

^{**}Corrected for oversize, when oversize particles exceed 5% of sample.

Report Reviewed By:

*Specific Gravity of Soils Estimated and Specific Gravity of Oversize Estimated.

PDF

This report shall not be reproduced, except in full, without written permission from Advance Testing Company, Inc.

The results in this report relate only to the items inspected or tested.

^{**}Material was oversaturated at 11.3% moisture